

Xerox® DocuMate® 4790

Reliable High-Speed Scanner Increases Office Efficiency

- 90 ppm / 180 ipm* at 200 dpi
- A3 (11" x 17") paper size
- ADF holds 200 pages†
- LCD Front Panel for job control, status and alerts
- Ultrasonic double feed detection sensor
- Create searchable PDF files to make it easy to find scanned documents
- Pre-Imprinter (sold separately)
- Color Space Compatibility with Xerox® iGen® Digital Press
- Xerox® FreeFlow Makeready® Supported

*Landscape US letter and A4, b&w, grey & colour.
† 20 lb., 75-80 g/m² paper



Equipment You Can Depend On

The Xerox® DocuMate® 4790 is the ideal scanner for both large-volume and distributed scanning environments. It has a duty cycle of up to 15,000 sheets per day and has been engineered with innovative features for easy operation and productive batch scanning, including stapled document, ultrasonic double feed detection and support for long document scanning.

A highly reliable and compact document scanner, the Xerox® DocuMate® 4790 scans up to 90 ppm and 180 ipm and includes a 200-page Automatic Document Feeder that accepts up to A3 (11" x 17") size documents and can handle nearly any mix of paper in various sizes and thicknesses. Its unique paper feed mechanism minimises the possibility of damaging important documents and ensures precise feeding to make your office work even more efficient. The roller is designed for efficiency by separating itself from the page each time a sheet is fed, reducing the likelihood of drag and double feeds, and improving the useful life of the roller. A separate double feed prevention roller applies controlling pressure when paper 'sliding' (caused by buildup of toner or carbon on the rollers) is detected.

The scanning glass is protected by the use of various sensors that detect stapled pages and automatically interrupt the scan process. It is also equipped with ultrasonic multi-feed detection and an innovative self-cleaning function that removes dust from the scanning glass to ensure consistently high image

quality. The Xerox® DocuMate® 4790 has a convenient clamshell design that allows direct and straightforward access to the entire paper path, so a user can clear paper jams, clean the unit, or replace rollers easily without having to call a service technician. A pre-scan imprinter is also available for the Xerox® DocuMate® 4790 and is supported through the included TWAIN™ and ISIS® drivers.

Intuitive Tools and Design

The Xerox® DocuMate® 4790 provides both high-quality image enhancement and increased productivity with Kofax® VRS™ Professional AIPE-EBC for auto-everything scanning, including Auto Rotation, Blank Page Deletion and Auto Color Detect. VRS Professional improves your workflow and reduces the total time required to finish even the largest batches of mixed documents. TWAIN and ISIS drivers are included to ensure compatibility with document management software and your capture applications. The DocuMate 4790 is powered by Visioneer® OneTouch® scanning technology for simplifying scan jobs and workflow. The scanner also has an easy-to-read LCD on the front that reminds the user of the resolution, color mode, file type, processing and final destination of the scanned document.

You'll find the Xerox® DocuMate® 4790 to be the kind of advanced and reliable equipment you expect to come from Xerox. We wouldn't have it any other way.

Xerox® DocuMate® 4790

Image Enhancement Technology

Visioneer® OneTouch® is integrated with image enhancing software such as Visioneer Acuity with DriverPLUS or Kofax® VRS™ (VirtualReScan), model dependent. Using advanced algorithms and dynamic thresholding, these software tools effectively improve the visual clarity of every document that you scan, applying intelligent correction to imperfect images, increasing OCR accuracy, and saving time.

Nuance® Searchable PDF Solution

Nuance OmniPage® and PDF Converter provide everything you need to create, convert, edit, assemble and securely share searchable PDF files with precision OCR analysis, advanced layout detection and Logical Form Recognition™ (LFR) technology. Combining powerful functionality, superior Microsoft® Office® support and DMS integration into one package.

Office Gemini

Dokmee Capture

Dokmee Capture high production scanning software provides all the features required for document capture, processing and reporting. It allows businesses both large and small to easily convert their scanned documents into digital files, capture images and data contained in them, and then transform it into organised searchable information. This mission-critical business information is then placed into a centralised location to be easily searched, stored and retrieved when needed. Dokmee Capture is the perfect answer for companies in any industry needing to catch up on a backlog of converting paper files to electronic images.

DocuMate 4790 Product Specifications	
Model Number w/VRS Pro	100N02781
Model Number w/VRS Basic	100N02824
Scan Speed	90 ppm / 180 ipm (black & white, greyscale, or colour at 200 dpi, landscape A4, 8.5" x 11" US letter) 70 ppm / 140 ipm (black & white, greyscale, or colour at 300 dpi, landscape A4, 8.5" x 11" US letter)
Scan Method	Automatic Document Feeder (ADF)
Imaging Sensor	Dual Charge-Coupled Device (CCD)
Light Source	White LED light source
Background	Switchable black or white background
Optical Resolution	600 dpi
Output Bit Depth	24-bit colour, 8-bit greyscale, 1-bit black & white
Other functions	Length control, barcode detection (ISIS), patch code detection, Automation separation, control sheet, long paper mode
Interface	Hi-speed USB 2.0 (1.1 compatible)
Detection	Ultrasonic double feed detection, stapled document detection
Accessories	DocuMate 4700 flatbed scanner, Pre-Scan Imprinter
ADF Minimum Document Size	48 mm x 70 mm (1.9" x 2.8")
ADF Maximum Document Size	305 x 432 mm (12" x 17"); Custom sizes up to 305 x 2540 mm (12" x 100")
ADF Capacity	200 sheets (20 lb., 75-80 g/m ² paper)
Document Weight	20 - 157 g/m ² (5 - 42 lbs.)
Document Thickness	1.6 - 7.9 mils (0.04 - 0.2 mm) Note: 1 mil = 0.001"
Duty Cycle	15,000 pages/day
Power Requirement	AC 100 – 240 V, 50/60 Hz
Power Consumption	Maximum (Scanning) 100 watts Minimum (Standby) 35 watts Sleep Mode 3.5 watts or less
Operating Environment	Temperature: 59°F - 86°F (15°C - 30°C) Humidity: 20 - 80% RH
Storage Environment	Temperature: 32°F - 104°F (0°C - 40°C) Humidity: 10 - 80% RH
Dimensions (w x d x h)	468 x 444 x 339 mm (18.5" x 17.5" x 13.4")
Weight	18 kg (40 lbs.)

Box Contents

- DocuMate 4790 Scanner
- Quick Installation Guide
- Technical Support Card
- Blower w/Brush
- Roller Cleaning Paper, Cleaning Paper Card
- Shading Sheet, Shading Caution Leaflet
- DFP (Double Feed Protection) Roller
- AC Power Cord US (1), Euro/UK (2)
- USB Cable
- DVD-ROM including:
 - User's Manual
 - Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU**
 - Nuance® OmniPage® Pro
 - Office Gemini Dokmee Capture*
 - Nuance PDF Converter
 - Visioneer OneTouch
 - Visioneer Acuity
 - Scanner Drivers: TWAIN™, EMC Captiva ISIS®, Microsoft® Windows® Image Acquisition (WIA) Driver, Visioneer DriverPLUS

PC Minimum System Requirements

- Intel® Pentium® 4 or equivalent processor
- Windows 8 / 7 / Vista® / XP®
- 2GB RAM
- 350 MB available hard disk space
- DVD-ROM drive
- USB port

Consumables

- 4790ROLL-KIT – User installable roller assembly. Roller kit will last up to 350,000 scans depending on scanning conditions.

* Dokmee Capture is not supported on Microsoft Windows XP.

** Bundled VRS 4.5 is not compatible with the Windows 8 Operating system.

For more information about the Xerox line of scanners, visit www.xeroxscanners.co.uk



©2013 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design® and DocuMate® are trademarks of, or licensed to Xerox Corporation in the United States and/or other countries. Visioneer® and Visioneer One Touch® are trademarks of Visioneer, Inc. Nuance® PaperPort® and OmniPage® are trademarks of Nuance Communications, Inc. or its affiliates in the United States and/or other countries. Microsoft®, Windows Vista®, Windows®, the Windows logo and XP® are trademarks of Microsoft Corporation in the United States and/or other countries. Intel® and Pentium® are trademarks of Intel Corporation in the U.S. and/or other countries. TWAIN™ is a trademark of TWAIN Working Group. EMC®, ISIS® and QuickScan™ are trademarks of EMC Corporation. Universal Serial Bus is a trademark of USB Implementers Forum, Inc. (USB-IF). All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox products and services are subject to change without notice. BR 7748_100N02781_270714

